http://www.jourmag.org/index.php/jma

Journal of Magnetism and Its Applications

Received November 5th 2023 received in revised December 10th 2023 accepted December 24th 2023

Research articles

Current Induced Spin–Orbit Torques in Ferromagnetic Systems

Emma J. Walker
Department of Materials Science, University of Cambridge, UK

Article info

Keywords:
spin–orbit torques,
ferromagnet,
spin Hall effect,
Rashba effect,
magnetization dynamics,
heavy metals,
spintronics,
torque efficiency

Abstract

Current induced spin–orbit torques (SOTs) in ferromagnetic systems have emerged as a promising route for efficient manipulation of magnetization in spintronic devices. These torques arise from strong spin–orbit coupling in heavy metal/ferromagnet heterostructures and can enable low power, high speed switching of magnetic bits without applied magnetic fields. This article reviews the fundamental mechanisms of SOTs, including the spin Hall and Rashba–Edelstein effects, and examines their influence on magnetization dynamics. We discuss experimental techniques for characterizing SOTs, key material systems that exhibit strong torques, and challenges for device integration. The analysis highlights recent advancements in engineering large effective fields and optimizing torque efficiency for application in memory and logic technologies.

Introduction

The ability to control the magnetic state of a ferromagnet using electrical currents has revolutionized spintronics, the field focused on harnessing the spin degree of freedom for information technologies. Traditional magnetic switching relies on magnetic fields, which are difficult to scale for dense devices. Current induced spin–orbit torques (SOTs), however, provide an electrically driven mechanism that leverages intrinsic spin–orbit coupling to exert torques on magnetization without external magnetic fields. These torques originate from phenomena such as the spin Hall effect (SHE) in heavy metals and the Rashba–Edelstein effect at interfaces with structural inversion asymmetry. The effective fields generated by SOTs can switch magnetic moments, drive domain wall motion, and enable high frequency magnetization dynamics. This article synthesizes current understanding of SOT physics, materials, characterization techniques, and technological prospects.

Spin Orbit Coupling and Origins of Spin–Orbit Torques

Spin–orbit interaction is a fundamental phenomenon in which an electron's spin is coupled to its momentum, leading to spin-dependent transport phenomena. In the context of spin–orbit torques (SOTs), this coupling is primarily observed in materials with strong spin–orbit coupling (SOC), such as heavy metals like platinum (Pt), tantalum (Ta), and tungsten (W). These materials are often integrated with ferromagnetic layers in heterostructures. When an electric current flows through these heavy metals, the spin Hall effect (SHE) generates transverse spin currents perpendicular to the charge current. The interaction of these spin currents with adjacent ferromagnetic layers induces torques that can control the magnetization of the ferromagnet. At the interfaces of these materials, where inversion symmetry is broken, Rashba–Edelstein effects also contribute to the generation of spin currents. These spin currents exert spin–orbit torques that can either switch the magnetic orientation or alter its precession dynamics. This combination of effects forms the core mechanism by which SOTs operate in spintronic devices.

Mechanisms of Torque Generation

Spin–orbit torques are generally described by two main components: the damping-like torque (τ_{DL}) and the field-like torque (τ_{FL}). The damping-like torque, which is most efficient for switching the magnetization of a ferromagnetic layer, is often linked to the spin Hall effect (SHE) and can be seen as a torque that works to align the magnetization of the ferromagnet with the spin current direction. It is typically perpendicular to both the magnetization and the spin current, promoting magnetization switching when the current is sufficiently strong. On the other hand, the field-like torque (τ_{FL}), which influences the precession of the magnetization but is less efficient for switching, arises primarily from the Rashba–Edelstein effect. This torque is oriented more like an effective magnetic field and contributes to the rotation of the magnetization vector in a direction similar to the applied current flow. These two torques, with different characteristics, play complementary roles in the manipulation of magnetization dynamics in spintronic devices, such as magnetic random-access memory (MRAM) and domain-wall logic devices.

Materials with Enhanced Spin–Orbit Torques

The efficiency of spin–orbit torques is heavily dependent on the materials used in the device structure. Heavy metals such as platinum (Pt), tungsten (W), and β-tantalum (β-Ta) have long been recognized for their large spin Hall angles, making them excellent candidates for generating large spin currents. The spin Hall angle is a key parameter that determines the efficiency with which charge currents can be converted into spin currents. Additionally, materials with topologically protected states, such as topological insulators and certain two-dimensional (2D) materials like graphene and transition metal dichalcogenides (TMDs), offer enhanced spin–orbit coupling and thus increased torque efficiency. Engineering the interfaces between ferromagnetic materials and these heavy metals, such as by introducing oxide layers or creating heterostructures, can further enhance the effectiveness of the spin–orbit torques. Alloying with other elements or modifying the crystal structure at the interfaces also holds the potential to optimize the strength of the torques, enabling the development of highly efficient spintronic devices that are both low power and high speed.

Experimental Techniques

The experimental characterization of spin–orbit torques requires sophisticated techniques that can isolate and measure the contributions of both damping-like and field-like torques. One commonly used method is spin-torque ferromagnetic resonance (ST-FMR), which allows the measurement of the resonance frequency shifts in a ferromagnet under the influence of spin–orbit torques. This technique provides insight into

*Corresponding author
Email: ejw22@cam.ac.uk

DOI: 10.53533/JMA.v2i1.19

the dynamics of the magnetization and the efficiency of the torques. Harmonic Hall measurements are also widely used to measure spin–orbit torques by detecting the voltage generated by spin currents in the Hall bar configuration. This method helps to quantify the magnitude of the torques and their dependence on current density and material properties. Additionally, time-resolved Kerr microscopy offers a direct observation of the magnetization dynamics at ultrafast timescales, enabling real-time visualization of the switching process and the influence of spin–orbit torques on the magnetization. These experimental techniques are essential for understanding the fundamental behavior of SOTs and for optimizing materials and device architectures in spintronics.

Technological Integration and Challenges

Spin–orbit torques hold great promise for a variety of spintronic applications, including magnetic random-access memory (SOT-MRAM), domain-wall logic, and neuromorphic computing. SOT-MRAM, in particular, leverages the ability of SOTs to switch the magnetization of a ferromagnetic layer with minimal power consumption, making it a potential candidate for non-volatile memory technologies. Domain-wall logic, which utilizes the motion of magnetic domain walls driven by SOTs, is a novel approach to logic circuits that could enable faster and more energy-efficient computing. However, despite their potential, several challenges remain in the technological integration of SOTs into practical devices. One significant issue is the high current density required to efficiently switch the magnetization, which can lead to power dissipation and thermal instability. Controlling the thermal effects and ensuring the long-term reliability of SOT-based devices is a critical challenge. Moreover, integrating these devices with complementary metal-oxide-semiconductor (CMOS) processes, which are essential for large-scale production and compatibility with existing technologies, remains an ongoing challenge. Continued research into new materials, device architectures, and fabrication techniques will be necessary to overcome these hurdles and realize the full potential of spin–orbit torques in next-generation spintronic applications.

Spin–Orbit Torque Efficiency and Scalability

The efficiency of spin–orbit torques (SOTs) is a crucial factor in determining the practicality and performance of SOT-based devices in commercial applications. The spin Hall angle, which quantifies the strength of spin–orbit coupling, is one of the key parameters that dictate the torque efficiency. A higher spin Hall angle enables more efficient conversion of electrical current into spin currents, which in turn produces stronger torques. The thickness of the heavy metal layer, typically chosen for its strong spin–orbit coupling, also plays an essential role. As the thickness of the heavy metal layer increases, spin current absorption becomes more effective, up to a point where further increases may lead to diminishing returns due to spin diffusion length limitations. Additionally, the quality of interfaces between the ferromagnetic and non-magnetic materials is vital for efficient torque generation. Imperfect interfaces can cause scattering of spin currents, reducing the effectiveness of the generated torques. Optimizing these material parameters, along with the intrinsic spin–orbit coupling strength of the materials involved, can lead to higher torque efficiency and better performance in spintronic devices. However, scaling these devices down to nanoscale dimensions presents challenges, particularly in maintaining high performance as device sizes shrink. At smaller scales, the effects of material defects, rough interfaces, and enhanced thermal fluctuations become more prominent, necessitating further refinement in materials and fabrication processes to ensure consistent and efficient performance in high-density devices.

Impact of Temperature and Strain on Spin–Orbit Torques

While temperature and strain are often considered secondary factors in the performance of spintronic devices, they have a profound impact on the efficiency of spin–orbit torques. As temperature increases, the spin Hall angle of many materials decreases, which can reduce the torque efficiency. Elevated temperatures can induce a reduction in the spin–orbit coupling strength, affecting the generation and transport of spin currents. This is especially important in devices that are required to function at high temperatures, such as in automotive or industrial applications, where temperature stability is crucial. On the other hand, mechanical strain can be employed as a tuning parameter to enhance the efficiency of spin–orbit torques. Strain engineering, which involves applying controlled mechanical stress to a material, can modify the electronic band structure, potentially increasing the spin Hall angle or adjusting the magnetic properties of the ferromagnetic layers. By introducing strain at the interface between materials, the overall spin–orbit coupling can be strengthened, leading to enhanced torque generation. However, the relationship between strain and spin–orbit torque efficiency is complex, and the effect is highly dependent on the materials and the direction of the applied stress. Therefore, understanding the interplay between temperature, strain, and spin–orbit torques is critical for developing devices that are both thermally stable and capable of high performance under various environmental conditions.

Role of 2D Materials and Van Der Waals Heterostructures

In recent years, two-dimensional (2D) materials such as graphene, transition metal dichalcogenides (TMDs), and topological insulators have attracted significant attention in spintronic research due to their unique electronic properties, including strong spin–orbit coupling, high carrier mobility, and tunable band gaps. These materials offer a new frontier for enhancing spin–orbit torques, as their intrinsic properties can be easily modified by external factors such as electric fields, strain, and gating, enabling highly controllable spintronic behavior. 2D materials, especially those with strong spin–orbit interactions, can be incorporated into SOT devices to enhance the overall torque efficiency. The combination of 2D materials with ferromagnetic layers in van der Waals heterostructures provides a particularly exciting avenue for advancing spintronics. In these heterostructures, the materials are stacked together without the need for chemical bonding, allowing for the preservation of the individual properties of each material. The synergy between the strong spin–orbit coupling in 2D materials and the ferromagnetic layers can lead to the generation of spin currents with greater efficiency, as well as the development of new types of SOT devices with improved performance. Topological insulators, for instance, exhibit surface states that are protected by time-reversal symmetry, offering robust spin-polarized currents that can be utilized for generating spin–orbit torques. The integration of 2D materials into traditional spintronic devices could also pave the way for new applications, such as topological spintronics and devices that exploit the quantum properties of 2D materials. This approach represents a promising direction for the future of spintronics, where the versatility and tunability of 2D materials open up a host of possibilities for enhancing torque efficiency and developing next-generation spintronic technologies.

Summary

Current induced spin–orbit torques represent a key mechanism for low energy control of magnetization in ferromagnetic systems. The interplay between spin Hall and interface effects allows electrical currents to generate effective fields that can switch magnetic states or drive dynamic responses. Understanding the material dependence of torques and optimizing fabrication are crucial for advancing spintronic devices. Ongoing research targets materials with large spin Hall angles, interface engineering for stronger torques, and novel measurement techniques to accurately quantify torque contributions. Future spintronic technologies, including non volatile memories and logic architectures, stand to benefit from the continued refinement of SOT mechanisms and materials systems.

References

[1] Manchon, A., & Zhang, S. (2009). Theory of spin torque due to spin–orbit coupling. Physical Review B, 79(9), 094422.
[2] Miron, I. M., et al. (2010). Current driven spin torque induced by the Rashba effect in a ferromagnetic metal layer. Nature Materials, 9(3), 230–234.
[3] Liu, L., et al. (2012). Spin torque switching with the giant spin Hall effect of tantalum. Science, 336(6081), 555–558.
[4] Garello, K., et al. (2013). Symmetry and magnitude of spin–orbit torques in ferromagnetic heterostructures. Nature Nanotechnology, 8, 587–593.
[5] Sinova, J., et al. (2015). Spin Hall effects. Reviews of Modern Physics, 87(4), 1213–1260.
[6] Fan, Y., & Wang, K. L. (2016). Spin orbit torque efficiency in ferromagnetic heterostructures. APL Materials, 4(3), 032303.
[7] Qiu, X., et al. (2018). Spin–orbit torque in heavy metal/ferromagnet interfaces. Applied Physics Reviews, 5(4), 041103.
[8] Zhang, W., et al. (2020). Review of spin–orbit torque materials. Materials Today Physics, 15, 100262.
[9] Pai, C. F., et al. (2015). Spin transfer torque devices utilizing the spin Hall effect. Journal of Applied Physics, 117(17), 172615.
[10] Han, J., et al. (2017). Advanced materials for efficient spin–orbit torque. Nature Materials, 16(9), 913–919.
[11] MacNeill, D., et al. (2017). Control of spin–orbit torques through crystal symmetry in WTe2. Nature Physics, 13(3), 300–305.
[12] Garello, K., & Gambardella, P. (2019). Magnetization dynamics driven by spin–orbit torques. Journal of Physics: Condensed Matter, 31(8), 083001.